



Part No.	No. of Chips	Material	Emitter Color	Lens Type	Wave Length λ_p (nm)	At 20mA		View Angle $2\theta_{1/2}$ (deg)	Package Dimension
						Vf (V) Type	Iv (mcd) Type		
U260UIC-5	1	---	Orange/Red	Water Clear	640	1.9	1200	70	
U260UOC-5	1	---	Orange	Water Clear	600	1.9	1200	70	
U260UYC-5	1	---	Yellow	Water Clear	595	2	1200	70	
U260UGC-5	1	---	Green	Water Clear	575	2.1	160	70	
U260ZGC-5	1	---	Green	Water Clear	525	3.2	1300	70	
U260UBC-5	1	---	Blue	Water Clear	460	3.4	350	70	
U260UWC-5	1	---	White	Water Clear	X=0.22~0.36 Y=0.22~0.38	3.5	1900	70	
U261BRAGC-5	1	---	Red	Water Clear	643	1.9	1200	80	
	1	---	Pure Green	Water Clear	525	3.2	1100	80	
	1	---	Blue	Water Clear	465	3.3	300	80	
U261UIC-5X3A	3	---	Orange/Red	Water Clear	640	1.9	3400	80	
U261UOC-5X3A	3	---	Orange	Water Clear	600	1.9	3400	80	
U261UYC-5X3A	3	---	Yellow	Water Clear	595	2	3400	80	
U261UGC-5X3A	3	---	Green	Water Clear	575	2.1	550	80	
U261ZGC-5X3A	3	---	Green	Water Clear	525	3.2	3900	80	
U261UBC-5X3A	3	---	Blue	Water Clear	460	3.4	1100	80	
U261UWC-5X3A	3	---	White	Water Clear	X=0.22~0.36 Y=0.22~0.38	3.5	6400	80	

NOTES:

1. All dimensions are in millimeters.
2. Tolerance is +/- 0.2mm unless otherwise specified
3. Protruded resin under flange is 1.5mm MAX.
4. Specifications are subject to change without notice.